

## Generador Silencioso - Bencina

2. Generador a Bencina  
Cantidad: 4 unidades



Model		FG3000is
Engine	Type	Forced Air-Cooled, 1-Cylinder, 4-Stroke, OHV
	Displacement	192 cc
	Rated power output	3.8 KW/3600RPM
	Max. power output	3.9 KW/3700RPM
	Bore*Stroke(mm)	70 X 50
	Ignition system	T.D.I
	Starting system	Recoil start/ <b>Electric start</b>
	Fuel tank capacity	15 L
	Fuel consumption	400g/kw.h
	Continous operating (70% of rated load)	18 h
	Noise (7m away)	60 dba
Generator	Rated output frequency	60/50 HZ
	Rated A.C. Output	110/220V
	D. C. Output	12 V, 8.3 A
	Rated power output(KVA)	2.8 KW
	Max. power output(KVA)	3KVA
Dimensions	Length*Width*Height	580*320*425 mm
	Net weight / Gross weight	49/51 kg
	Packing size(mm)	600*340*440 mm
Features	Fuel gauge	Y
	Auto voltage adjustor	Y
	Low oil alert	Y
	Circuit protector	Y
	Parallel connection capability	Y
	Quantity	4
	Certificates	CE, GS, Euro II, ETL, EPA, CARB, Noise level