

HG6500E3**Cantidad : 1****Bencia y gas
No silencioso**

Model	HG6500SE3	
Rated frequency (Hz)	50	60
Rated output (kVA)	6,2	6,8
Max. output (kVA)	6,8	7,5
Rated Voltage (V)	230/400	240/416
Rated rotation speed (r/min)	3000	3600
Phase NO.	Three-phase	
Power factor (Cos Φ)	0.8(lag)	
Insulation Grade	B	
Pole number	2	
Excitation mode	Self-excitation & constant voltage (AVR)	
Panel Type	General Panel	
Voltage (V)	230/400	240/416
Receptacle	One single-phase and one three-	
Connection pole	Without	
DC12V output	Connection pole output	
Overall dimen (LxWxH) (mm)	950*590*785	
Dry weight(kg)	132	
Working assorting weight (Kg)	142	
Noise level (7m) dB(A)	65	
Structure type	Silent	

Engine Model	FG188FGE	
Engine Type	Single cylinder, air cooled, four-stroke, OHV	
Cylinder NO.-bore×stroke (mm)	1-88×64	
Displacement (ml)	390	
Rated power [KW/(r/min)]	7.5/3000	8.2/3600
Compression ratio	8.5:1	
Rated rotation speed (r/min)	3000	3600
Combustion system	T.C.I	
Cooling system	Air cooled	
Lubrication system	Splashed	
Starting system	Recoil starter or electric starter	
Fuel type	Automatic unleaded gasoline	
Lube oil brand	CD grade or SAE10W-30, 15W-40	
Capacity of cooling water (L)	N/A	
Lube capacity (L)	1,1	
Starting motor capacity (V-kW)	12V 0.4kW	
Charging generator capacity (V-A)	12V 8A	
Battery capacity (V-Ah)	12V /12Ah	
Fuel consumption (g/kW.h)	≤374	
Fuel tank capacity (L)	15	
Continuous running time (hr)	4,5	4,5